

## Zirkon<sup>®</sup> Gas ClO<sub>2</sub>

Kuntze Gas sensors are amperometric sensors for the detection of chlorine dioxide gas. The matching fitting Ne GSH allows for an easy installation of the gas sensor.

### Advantages

- > Short response times
- > High reliability
- > Simple start-up due to printed calibration value

### Zirkon<sup>®</sup> Gas ClO<sub>2</sub>



Artikelnummer: 29111011K

### Measurement Parameter

- > Chlorine Dioxide: 0.. 5 ppm\*  
\*Range of measurement device can deviate.

### Process Conditions

- > Temperature: -20.. +50 °C (4..122 °F)
- > Humidity: 15.. 90 % rH (non condensating)
- > Storage Life: 6 months in container at +4..10 °C
- > Influence of Humidity: No effect on the zero point

### Cross Sensitivity Chlorine Dioxide sensor at 20 °C

Gas	Concentration	Value Read
Carbon Monoxide	100 ppm	0
Sulfure Dioxide	10 ppm	0
Nitrogen Monoxide	10 ppm	0
Hydrogen	300 ppm	0
Nitrogen Dioxide	5 ppm	~5
Chlorine	20 ppm	~20
Hydrogen Sulfide (H <sub>2</sub> S) *		ND*

\* Contact with H<sub>2</sub>S poisons the sensor, subsequent contact with chlorine dioxide reactivates it.

The influencing factor can vary from sensor to sensor and over the life span of the individual sensor. No claim to completeness of the data, the sensors can potentially exhibit cross sensitivity to other gases.



**Kuntze Instruments GmbH**

Robert-Bosch-Str. 7a  
40688 Meerbusch  
Germany

+49 2150 70660  
info@kuntze.com  
www.kuntze.com