

## 5SCR-M12-AE-X

Screened cable for connecting DES sensors with M12 plug, available in 5 or 10 m length.

### Advantages

- > Screened
- > M12 plug
- > Wire end ferrules

### Technical data

#### Ambient conditions

- > Ambient temperature: -20.. +70 °C

#### Mechanical Construction

- > Material: PVC

#### Articlenumber:

**44136406K:** Type: 5SCR-M12-AE-1,0,  
Description: Connection cable for double gold or double platinum sensors, 1 m

**44136411K:** Type: 5SCR-M12-AE-5,  
Description: connection cable for double gold or double platinum sensors, 5 m

**44136412K:** Type: 5SCR-M12-AE-10,  
Description: connection cable for double gold or double platinum sensors, 10 m

**44136413K:** Type: 5SCR-M12-AE-50,  
Description: Connection cable for double gold or double platinum sensors, 50 m

### 5SCR-M12-AE-X



Plug	Cable	DIS Sensor		Pt 55 W		Gas Sensor
		Neon	Neon Multi	Neon	Neon Multi	Neon
1	Brown	2	2	7	20	1 [4"]
2	White	3	3	9	21	2 [5"]
3	Black	-	-	50	50	-
4	Blue	4	4	51	51	-
5	Grey	-	-	-	-	3 [5"]
Shield	Metal	1	1	-	-	-

\*Only for Second Gas Sensor



**Kuntze Instruments GmbH**

Robert-Bosch-Str. 7a  
40688 Meerbusch  
Germany

+49 2150 70660  
info@kuntze.com  
www.kuntze.com