

5SCR-M12-AE-X

Screened cable for connecting DIS sensors with M12 plug, Pt 55 W and Gas Sensor holder, available in 1,2m, 5m, 10m or 50 m length.

44136412K: Type: 5SCR-M12-AE-10,
Length: 10 m

44136413K: Type: 5SCR-M12-AE-50,
Length 50 m

Advantages

- > Screened
- > M12 plug
- > Wire end ferrules

Technical data

Ambient conditions

- > Ambient temperature: -20.. +70 °C/ -4..158 °F

Mechanical Construction

- > Material: PVC

Articlenumber:

44136407K: Type: 5SCR-M12-AE-1,2,
Length 1,2 m

44136411K: Type: 5SCR-M12-AE-5,
Length 5 m

5SCR-M12-AE-X



Plug	Cable	DIS® Sensor		Pt 55 W		Gas Sensor holder
		Neon®	Neon Multi®	Neon®	Neon Multi®	Neon®
1	Brown	2	2	7	20	1 (4*)
2	White	3	3	9	21	2 (5*)
3	Black	/	/	50	50	/
4	Blue	4	4	51	51	/
5	Gray	/	/	/	/	3 (6*)
Shield	Metal	1	1	/	/	/

*Only for second Gas Sensor



Kuntze Instruments GmbH
Robert-Bosch-Str. 7a
40688 Meerbusch
Germany

+49 2150 70660
info@kuntze.com
www.kuntze.com