

Zirkon® pH Process HT

Kuntze sensors stand for quality and are manufactured by our own production. Made in Germany.

Zirkon® pH Process HT is a high temperature specialist can be used for professional applications, such as sterilization.

Advantages

- > Thermally stable up to 130 °C
- > Low maintenance
- > Dirt-repellent and corrosion resistant Zirkon junction
- > High accuracy through the use of high alkali high temperature glass

Measuring Parameter

- > pH-Value: pH 0...14

Process Conditions


- > Max. Pressure: < 13 bar at 135 °C
- > Min. Conductivity: > 150 µS/cm
- > Temperature: -20...+130 °C

Mechanical Construction

- > Junction: Zirkon
- > Shaft Material: Glass
- > Shaft Length: 225 mm
- > Shaft Diameter: 12 mm
- > Electrode Material: AH-Glass-Ball
- > Reference System: Ag / AgCl / Solid electrolyte
- > Process Connection: S8 Plug
- > Electrical Connection: 2 Poles
- > Temperature Sensor: None
- > Installation Depth: 225 mm
- > Potential Compensation: None

Article No.: S24132141K
Order Code: 208015100

Mechanical Drawing





Kuntze Instruments GmbH
Robert-Bosch-Str. 7a
40688 Meerbusch
Germany

+49 2150 70660
info@kuntze.com
www.kuntze.com